

#### **ATTACHMENT 2**



International Motors, LLC is pleased to provide you with this proposal compliant with all terms of the Sourcewell Vehicles and Chassis Contract #032824-NVS awarded fromerly to Navistar, Inc now International Motors, LLC for new International truck(s). If you have any questions regarding enrollment in Sourcewell or detailed contract terms and conditions, please see your local International Dealer sales representative.

#### PROPOSAL PREPARED FOR:

#### PROPOSAL PREPARED BY:

Sourcewell Member:	Sweetwater Authority	Westrux Intl
Contact:	David McCain	Lucas Berry
Address:	744 F St.	2200 E. Steel Rd
City/State/Zip:	Chula Vista, CA 91910	Colton, CA 92324
Phone:	(619) 420 - 1413	(760)567-2294
Email:	dmccain@sweetwater.org	Lberry@westrux.com

Proposal Number	27463
Date	8/4/2025
Quantity of this Specification	1
Single Sourcewell Transaction Total Volume	1

Chassis		
New 2026 International HX620 /S13 Chassis	\$	333,293.00
Base Chassis List \$ 255,482.00		
Options List \$ 77,811.00		
Sourcewell Contract Discount 49.1%	\$	(163,646.86
Volume Incentive	\$	
Material Price Increases	\$	9
Net Sourcewell Chassis Price	\$	169,646.14
Sourcewell Partner Body		
	\$	-
	\$	-
Handling Fee 4.00%	\$	-
Non-Sourcewell Dealer Supplied Body		
D&H Truck Equipment Inc - BeauRoc 15 ft.	\$	59,945.00
	\$	2
Handling Fee 5.00%	\$	2,997.25
Additional Post Build Work		
Delivery Kit - Fire Extingusher & Flares, Floor Mats, Mud Flaps	\$	750.00
Wash and Detail	\$	200.00
	\$	-
Handling Fee 5.00%	\$	47.50
Service Contracts	_	
CARB COMPANION PLAN for CARB X15 Engines (CARB mandatory)	\$	1,000.00
	\$	*
	\$	2
Additional Freight		
Freight Colton to D&H, Then D&H to Colton	\$	1,000.00
Freight Colton to Sweetwater	\$	500.00
Additional Floorplan		
5 months	\$	7,275.00
	\$	*
Additional Fees & Taxes		
Chula Vista 8.75%	\$	21,305.67
Doc/DMV Fee	\$	132.50
	\$	
Final Sourcewell Per Vehicle Price FOB Colton, CA	\$	264,799.06
Final Sourcewell Total Vehicle(s) Price	\$	264,799.06
Additional Sourcewell Qualified Content		
	4	

Terms:

Silver Package Award

Stock unit in dealer's inventory, dealer will accept a final purchase order using the current Sourcewell pricing quoted above.

\$1,200

Dealer placing a new orders for the Sourcewell Member, the purchase order cannot be firmed up until the unit is slotted to build with a firm build date or lineset.

Once a firm build date has been established, dealer will provide the Sourcewell Member approved pricing and a final purchase order can be accepted with firm pricing.

Dealer cannot guarantee bodies and/or equipment pricing added to the chassis for a turnkey sale until chassis is lineset.

#### Attachment 2



# Hx620 SBA

Sales Proposal For:

Sweetwater Authority

Presented By: WESTRUX INT'L., INC.

Prepared For:
Sweetwater Authority
David McCain
744 F St.
Chula Vista, CA 91910-2006
(619)420 - 1413
Reference ID: 12 yd Dump

Presented By:
WESTRUX INT'L., INC.
Lucas Berry
15555 Valley View Ave.
Santa Fe Springs CA 90670 (562)404-1020

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

#### Model Profile 2026 HX620 SBA (HX620)

**AXLE CONFIG:** 

6X4

APPLICATION:

Construction Dump

MISSION:

Requested GVWR: 66000, Calc. GVWR: 66000, Calc. GCWR: 140000

Calc. Start / Grade Ability: 30.89% / 2.88% @ 55 MPH

Calc. Geared Speed: 79.5 MPH

**DIMENSION:** 

Wheelbase: 205.00, CA: 136.00, Axle to Frame: 69.00

ENGINE, DIESEL:

(Cummins X15 450V) Productivity Series, EPA 2024, 450HP @ 1900 RPM, 1750 lb-ft Torque @

900 RPM, 2000 RPM Governed Speed, 461 Peak HP (Max)

TRANSMISSION, AUTOMATIC:

(Allison 4500 RDS) 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with

PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway

CLUTCH:

Omit Item (Clutch & Control)

**AXLE, FRONT NON-DRIVING:** 

{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity

AXLE, REAR, TANDEM:

{Meritor RT-46-160} Single Reduction, 46,000-lb Capacity, Driver Controlled Locking Differential

in Forward-Rear and Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 4.56

CAB:

Conventional, Day Cab

TIRE, FRONT: TIRE, REAR: (2) 425/65R22.5 Load Range L HAC 3 (CONTINENTAL), 465 rev/mile, 68 MPH, All-Position (8) 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position {Hendrickson HMX EX 460} Walking Beam, 46,000-lb Capacity, 54" Axle Spacing, Rubber

SUSPENSION, REAR, TANDEM:

Springs, with Transverse Torque Rods, Rubber End Bushings

PAINT:

Cab schematic 100LZ

Location 1: 9219, Winter White (Std)

Chassis schematic N/A

Code

Description

HX62000

Base Chassis, Model HX620 SBA with 205.00 Wheelbase, 136.00 CA, and 69.00 Axle to Frame.

1AND	AXLE CONFIGURATION 6x4
	Notes : Pricing may change if axle configuration is changed.
ENGINE	
12EWX	ENGINE, DIESEL {Cummins X15 450V} Productivity Series, EPA 2024, 450HP @ 1900 RPM, 1750 lb-ft Torque @ 900 RPM, 2000 RPM Governed Speed, 461 Peak HP (Max)
12VJZ	EMISSION, CALENDAR YEAR (Cummins X15) EPA, OBD and GHG Certified for Calendar Year 2025
12XCP	CARB EMISSION WARR COMPLIANCE for Cummins X15 Engines Less than or Equal to 500 HP
12WZJ	CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal located on Driver Door
12WVH	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Door
10UAC	VEHICLE REGISTRATION IDENTITY ID for the State of California
12XBC	RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler
	<u>Includes</u> : RADIATOR HOSES Premium, Rubber
12THT	FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed
	Includes : FAN Nylon
12VBA	AIR CLEANER Dual, Polished Stainless Steel, One Mounted on Each Side of Cowl Ahead of The Doors
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12864	BLOCK HEATER, ENGINE {Phillips} 120V/1500W
	<u>Includes</u> : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door
12VGU	ENGINE CONTROL, REMOTE MOUNTED for X15 Engines

<b>TRANSMISS</b>	ION
------------------	-----

12WTA

12WBR

12WGA

12WYZ

**13WUC** 

13BEK	TRANSMISSION, AUTOMATIC (Allison 4500 RDS) 6th Generation Controls, Wide Ratio, 6-Speed with Double
	Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

FAN OVERRIDE Manual; with Electric Switch on Instrument Panel, (Fan On with Switch On) HOSE CLAMPS, RADIATOR HOSES, Mechanical Type; with Constant-Tension Functionality

Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System

RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General

Purpose Trucks, Construction, Package Number 223

**♠** INTERNATIONAL

#### Vehicle Specifications 2026 HX620 SBA (HX620)

August 04, 2025

Code Description

OBD001 NEUTRAL AT STOP 13WVW omit neutral at stop

13WCU OIL COOLER, TRANSMISSION (Modine) Remote Mounted; Not for use with Retarder, for Automatic

Transmission

13WYU SHIFT CONTROL PARAMETERS (Allison) 3000 or 4000 Series Transmissions, Performance Programming

13WLM TRANSMISSION OIL Synthetic; 63 thru 76 Pints

13WET TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series

Transmission

CLUTCH

11001 CLUTCH Omit Item (Clutch & Control)

REAR AXLES, SUSPENSIONS

14HRM AXLE, REAR, TANDEM {Meritor RT-46-160} Single Reduction, 46,000-lb Capacity, Driver Controlled Locking

Differential in Forward-Rear and Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 4.56

14UMX SUSPENSION, REAR, TANDEM {Hendrickson HMX EX 460} Walking Beam, 46,000-lb Capacity, 54" Axle

Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings

14WMK AXLE, REAR, LUBE (EmGard FE-75W-90) Synthetic Oil; 65 thru 89.99 Pints

14WBN DIFF. SWITCH CONTROLS Two Independent Switches for Control Traction Differentials on Tandem Rear

Axies, Mounted on Dash

14862 PDL WARNING BUZZER Power Divider Lock

14AJX SHIELD, TEMPERATURE SENSOR Mounted to Rear Axle

14WBV SHOCK ABSORBERS, REAR (4) for Hendrickson HMX Suspension Only, Mounted from Frame to Beam

14WCR TRANSVERSE TORQUE RODS (Hendrickson) TRAAX Rod, Transverse Only

**FRONT AXLES** 

2ARY AXLE, FRONT NON-DRIVING (Meritor MFS-20-133A) Wide Track, I-Beam Type, 20,000-lb Capacity

FRONT SUSPENSIONS

3AGA SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 20,000-lb Capacity, with Shock

Absorbers

CABS, COWLS, BODIES

16030 CAB Conventional, Day Cab

<u>Includes</u>

CAB REAR SUSPENSION Air

CLEARANCE/MARKER LIGHTS (5) LED Roof Mounted

: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window

: CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket;

Located Above Driver and Passenger

: COURTESY LIGHT (2) Driver and Passenger Door Mounted

: DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater

Dimming, Center Mounted, Integral to Console

: FLOOR COVERING Rubber, Black : GLASS, ALL WINDOWS Tinted **()** INTERNATIONAL

#### Vehicle Specifications 2026 HX620 SBA (HX620)

August 04, 2025

<u>Code</u> <u>Description</u>

: GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side

: GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side

: READING LIGHT, CAB Located in Overhead Console

: STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door

16XTM ACCESS, CAB Aluminum, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper

Cab

16BAM AIR CONDITIONER with Integral Heater and Defroster

<u>Includes</u>

: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

16VKK CAB INTERIOR TRIM Diamond, for Day Cab

16XXC COWL TRAY LID

16WLS FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

16GEG GAUGE CLUSTER Premium Level; English with English Electronic Speedometer

Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip

Hours, MPG, Distance to Empty/Refill for

: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure

Gauge, Primary and Secondary Air Pressure

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage

(Visual and Audible), Low Air Pressure (Primary and Secondary)

16HGN GAUGE, AIR APPLICATION

16HGH GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

16HGG GAUGE, OIL TEMP, ENGINE

16HGL GAUGE, OIL TEMP, REAR AXLE

16HLX GAUGE, VOLTMETER Auxiliary Gauge, Located in Center Panel. Standard Cluster Also Includes Digital

Voltage Readout

16SDC GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry

Mounted Left and Right Side at B-Pillar

16GHU GRAB HANDLE, CAB INTERIOR (2) Safety Yellow

16WHJ HOSE CLAMPS, HEATER HOSE (Breeze) Belleville Washer Type

16XJP INSTRUMENT PANEL Wing Panel

16HKT IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

16SNU MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes

6.5" x 6" Convex Mirrors, for 102" Load Width

<u>Notes</u>

: Mirror Dimensions are Rounded to the Nearest 0.5"

16SNX MIRROR, CONVEX, LOOK DOWN Right Side, Bright, 6" x 10.5"

16XRX MODESTY PANEL Painted

16VVA MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire

Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 6x2, 6x4

and 6x6 Axle Configurations, Does Not Include Lift Axles or Spare Wheels

<u>Code</u> 16LWL	<u>Description</u> SEAT, DRIVER {ISRI} Series 300, Air Suspension, High Back, Mordura, Single Chamber Lumbar, Inboard Armrest, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt
16SRM	SEAT, PASSENGER {National} Non Suspension, High Back with Integral Headrest, Mordura Cloth, with Fixed Back, with Under Seat Storage
16UZJ	STORAGE, REAR WALL Storage Pocket, Located on Back Wall Between Driver and Passenger Seats
16WCE	SUNSHADE, EXTERIOR Bright Stainless Steel, 13" Drop Sun Visor, with Amber Lights
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature
16XDD	WINDOW, REAR Polycarbonate Plastic Window, Shatter Resistant
16XWJ	WINDSHIELD WIPER BLADES Winter Type
FRAMES	
1CGD	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 12.50" x 3.750" x 0.500" (317.5mm x 95.25mm x 12.7mm); 480.8" (12212mm) Maximum OAL
1LTE	BUMPER, FRONT Contoured, Aluminum, Stainless Steel Clad, Heavy Duty
1AMS	CROSSMEMBER, FRAME TIE for Heavy Duty
1652	CROSSMEMBER, REAR Relocated to End of Frame
1WRW	TOW HOOK, FRONT (2) Frame Mounted; 80,000-lb. Total Capacity
1WXL	WHEELBASE RANGE 191" (485cm) Through and Including 236" (600cm)
BRAKES	
BRAKES 4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
7	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications  Includes BRAKE LINES Color and Size Coded Nylon PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel PARKING BRAKE VALVE For Truck QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6
7	Includes  : BRAKE LINES Color and Size Coded Nylon  : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  : PARKING BRAKE VALVE For Truck  : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4
4091	Includes  : BRAKE LINES Color and Size Coded Nylon  : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  : PARKING BRAKE VALVE For Truck  : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  : SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel
4091 4AZJ	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control
4091 4AZJ 4GBM	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double
4AZJ 4GBM 4XDT	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity
4AZJ 4GBM 4XDT 4EXV	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS (Bendix AntiLock Brake System) 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT (Meritor 16.5X6 Q-PLUS CAST) Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity  BRAKE CHAMBERS, FRONT AXLE (Bendix) 24 SqIn
4AZJ 4GBM 4XDT 4EXV 4LAA	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity  BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 Sqln  SLACK ADJUSTERS, FRONT {Haldex} Automatic
4AZJ 4GBM 4XDT 4EXV 4LAA 4WBX	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity  BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 Sqln  SLACK ADJUSTERS, FRONT {Haldex} Automatic  DUST SHIELDS, FRONT BRAKE for Air Cam Brakes  BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double
4AZJ 4GBM 4XDT 4EXV 4LAA 4WBX 4XDR	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity  BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 Sqln  SLACK ADJUSTERS, FRONT {Haldex} Automatic  DUST SHIELDS, FRONT BRAKE for Air Cam Brakes  BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle
4AZJ 4GBM 4XDT 4EXV 4LAA 4WBX 4XDR	Includes  BRAKE LINES Color and Size Coded Nylon  PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel  PARKING BRAKE VALVE For Truck  QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4  SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6  AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control  BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake  BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity  BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 Sqln  SLACK ADJUSTERS, FRONT {Haldex} Automatic  DUST SHIELDS, FRONT BRAKE for Air Cam Brakes  BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle  BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqln Spring Brake

6

46	INTERNATIONAL	
-	INTERNATIONAL	

August 04, 2025

<u>Code</u> 4SPA	Description AIR COMPRESSOR (Cummins) 18.7 CFM
4EDM	AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration
4VKC	AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab
4VKK	AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Right Rail, Back of Cab, Perpendicular to Rail
4WYZ	DRAIN VALVE (Bendix DV-2) (2) Automatic, with Heater, (2) Berg, with Pull Chains, for Air Tanks
4619	TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck
STEERING	
5PTB	STEERING GEAR (2) {Sheppard M100/M80} Dual Power
5710	STEERING COLUMN Tilting and Telescoping
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
DRIVELINES	
6DGU	DRIVELINE SYSTEM (Dana Spicer) SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4
EXHAUST SYSTEMS	
7BLY	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Cab Mounted Right Side
7BES	AFTERTREATMENT COVER Polished Aluminum
7SAP	ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ISX/X15 Engines; Furnished with Engine
7WBU	EXHAUST HEIGHT 11' 6"
7WBS	MUFFLER/TAIL PIPE GUARD (1) Bright Stainless Steel
7WBA	TAIL PIPE (1) Turnback Type, Bright
ELECTRICAL SYSTEMS	
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	Includes : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
8WXD	ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened
8GXJ	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount
8RPP	ANTENNA Shark Fin, Roof Mounted
8WDG	BACK-UP ALARM {Preco 1059} Electronic; Solid State, Dual Function, 112 dBA

4	INTERNATIONAL
45	INTERNATIONAL

August 04, 2025

Code 8VUK	<u>Description</u> BATTERY BOX Aluminum, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Right Side Back of Cab
8VUH	BATTERY BOX COVER Polished Aluminum
8XNB	BATTERY DISCONNECT SWITCH 300 Amp, Disconnects Power to Power Distribution Center (PDC), Does Not Disconnect Charging Circuits, Locks with Padlock, Cab Mounted
8MJU	BATTERY SYSTEM (Fleetrite) Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud
8HAE	BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/ Accessory Power/Ground and Sealed Connector for Stop/Turn
8RNB	CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror
8RGA	2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
8518	CIGAR LIGHTER Includes Ash Cup
8THN	HAZARD FLASHER OVERRIDE Hazard Flasher Overrides Brake Lights, To be Done with Programming System Controller
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position
8XKC	HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On
8836	HORN, AIR (2) Single Bell, Organ Tone, Extra Long, Chrome
8VAY	HORN, ELECTRIC Disc Style
8WZP	INDICATOR, BATTERY WARNING Green BATTERY ON Indicator, Mounted on Left Side of Instrument Panel, To be Used with Factory Installed or Customer Mounted Battery Disconnect Switch
8WBW	JUMP START STUD 12V, Remote Mounted
8XLW	LIGHT, WORK LED, Pedestal Mounted, Back of Cab, with Switch on Instrument Panel
8RPS	RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input
8RPB	RADIO, STEERING WHEEL CONTROLS Mounted in Steering Wheel, Radio Function Control Switch, Includes Volume Up/Down, Mute, Forward/Back and Bluetooth Answer/Disconnect
8695	SNOW SHIELD (2) Chrome; for Dual Air Horns
8RBZ	SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door
8RMZ	SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars
8WTL	STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection
8WPZ	TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
8TMG	TRAILER CONNECTION SOCKET {Phillips} 7-Way, Mounted at Rear of Frame, Wired for Turn Signals Combined with Stop, Compatible with Trailers with Combined Stop, Tail, Turn Lamps
8WEZ	TURN SIGNAL SWITCH Self-Canceling
8XPP	USB PORT Two USB-A Ports and Two USB-C Ports, Located in Instrument Panel
8WGL	WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

Code FRONT END	Description
9ASE	FRONT END Tilting, Composite
9WBD	BUG DEFLECTOR Stainless Steel, Mounted on Hood
9WAC	BUG SCREEN Mounted Behind Grille
9585	FENDER EXTENSIONS Rubber
9HCN	GRILLE Chrome Vertical Accent Bars, with Black Mesh
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
SPEEDOMETER, TOOL	S, MISC
10AGB	COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360
10WKN	KEYS - ALL ALIKE, ID I-1624 Compatible with Z-250
10WPR	MUD FLAP HOLDER Spring Loaded, Painted Black, with Red and White Reflective Tape, Less Flaps
10WSX	MUD FLAPS, REAR Black Poly, with International Logo, Less Holders
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
10SLV	PROMOTIONAL PACKAGE Government Silver Package
10WCY	SAFETY TRIANGLES
FUEL TANKS	
15SWJ	FUEL TANK Top Draw, Polished Aluminum, 26" Dia, 120 US Gal (454L), Mounted Left Side, Under Cab
15WEY	DEF TANK 10.8 US Gal (41L) Capacity, Frame Mounted Outside Left Rail, Under Cab
15BAA	DEF TANK COVER Stainless Steel
15LNA	FUEL HEATER PLUMBING (Cummins) Plumbing for Thermal Recirculation Valve (TRV) Mounted to Cummins X15 Engines, Thermostatically Controlled
15LPU	FUEL/WATER SEPARATOR {Racor 6600} Pre-Filter and Filter Base, Includes Water-in-Fuel Sensor
WHEELS, TIRES - FRON	т
27DJH	WHEELS, FRONT {Alcoa 82462} DISC; 22.5x12.25 Rims, High Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7752665441	(2) TIRE, FRONT 425/65R22.5 Load Range L HAC 3 (CONTINENTAL), 465 rev/mile, 68 MPH, All-Position
WHEELS, TIRES - REAF	3
28DWR	WHEELS, REAR (Accuride 43644) DUAL DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7372135439	(8) TIRE, REAR 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position
WHEELS MISC OPTION	S
29WLK	WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil

August 04, 2025

Code BODY INTEGRATION	<u>Description</u>		
60AKG	BDY INTG, PTO ACCOMMODATION for (3) Latched Rocker Switches, (1) PTO Switch, (2) Generic Switches to Control (3) 30 amp relays, with Programmable Interlocks, for Body Builder Hook up in the Engine Compartment Left Side, Recommended for Automatic Transmissions  Services Section:		
	Services Section:		
WARRANTY			
40132	WARRANTY Standard for HX520, HX620, Effective with Vehicles Built January 1, 2021 or Later, CTS-2015B		
40NSE	CARB COMPANION PLAN for CARB A26, S13 and X15 Engines		



ENOVEN SoCal Office: 619-794-7976 email: jaland@dhtruckequipment.com

Shop: 9779 Candida Street, San Diego CA 92126

# Quote

**Sold To:** 

Westrux

2200 E. Steel Rd. Colton CA 92324

Ship To:

Date: 08-24-2025

Phone: Fax:

PO#:
Terms:

Contact: Lucas Berry

760-567-2294

#### **Product/Services Sweetwater**

Qty		Ext. Cost
1	BeauRoc 15 foot 12 yard all Hardox construction dump body with the following: 36" sides, 44" rear, cab shield, spreader apron, ditch gate, electric tarp, Mailhot DA hydraulic cylinder, side step, DH hitch package with 370a hitch, HD hydraulic tank with sight/temp gauge, Chelsea hotshift PTO with direct mounted pump and remote valve-air shifted, strobe kit with hid-a-way fronts, mudflaps, cab controls, safety props, up lights, sealed clearance lights, complete installation and painted white to match cab.	59945.00
	Install 2 surface mounted strobe light heads in/on front hood/grille, install 2 rubber recessed strobe light heads facing rear in body corner posts.	Inc.



## LIMITED WARRANTY FOR HX \*Effective with vehicles built January 01, 2021 or later

#### **Basic Vehicle**

International®, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or RENEWED™ parts, based on the Component Coverages below.

Coverage	Months	Miles	Kilometers	Hours	Gross Discharge Throughput
Basic Vehicle Warranty	12	Unlimited	Unlimited	Unlimited	Unlimited
Basic Vehicle Warranty with Non-Navistar Engine	12	Unlimited	Unlimited	Unlimited	Unlimited
First 90 Days from Delivery to User (DTU) + Towing (Vehicle Down Warrantable Situations Only)	3	Unlimited	Unlimited	Unlimited	Unlimited
Brightwork, Chassis Paint and Corrosion (Other than Cab)	6	Unlimited	Unlimited	Unlimited	Unlimited
Hood/Cab Paint	12	Unlimited	Unlimited	Unlimited	Unlimited
Aluminum Cab/Cowl Perforation Corrosion	60	Unlimited	Unlimited	Unlimited	Unlimited
Steel Cab/Cowl Perforation Corrosion	120	Unlimited	Unlimited	Unlimited	Unlimited
Cab/Cowl Structure	60	Unlimited	Unlimited	Unlimited	Unlimited
Frame Side Rails	60	Unlimited	Unlimited	Unlimited	Unlimited
International A26 Engine	24	Unlimited	Unlimited	Unlimited	Unlimited
International A26 Engine (Rescue Applications)	60	100,000	160,000	Unlimited	Unlimited
Towing (Vehicles with International A26 Engine Failures Only)	24	Unlimited	Unlimited	Unlimited	Unlimited
International A26 Engine Major Components	60	500,000	800,000	Unlimited	Unlimited
Navistar N13 Engine	24	Unlimited	Unlimited	Unlimited	Unlimited
Navistar N13 Engine (Rescue Applications)	60	100,000	160,000	Unlimited	Unlimited
Towing (Vehicles with Navistar N13 Engine Failures Only)	24	Unlimited	Unlimited	Unlimited	Unlimited
Navistar N13 Major Components	60	500,000	800,000	Unlimited	Unlimited
International S13 Engine	24	Unlimited	Unlimited	Unlimited	Unlimited
International S13 Engine (Rescue Applications)	60	100,000	160,000	Unlimited	Unlimited
Towing (Vehicles with International S13 Engine Failures Only)	24	Unlimited	Unlimited	Unlimited	Unlimited
International S13 Engine Major Components	60	500,000	800,000	Unlimited	Unlimited
International T14 Transmission and Mounted PTO (Rear Axle Weight Ratings of 52,000 lb and Less)	36	Unlimited	Unlimited	Unlimited	Unlimited
Towing (Vehicles with International T14 Transmission Failures Only) (Rear Axle Weight Ratings of 52,000 lb and Less)	36	Unlimited	Unlimited	Unlimited	Unlimited
International T14 Transmission and Mounted PTO (Rear Axle Weight Ratings Greater than 52,000 lb)	24	Unlimited	Unlimited	Unlimited	Unlimited
Towing (Vehicles with International T14 Transmission Failures Only) (Rear Axle Weight Ratings Greater than 52,000 lb)	24	Unlimited	Unlimited	Unlimited	Unlimited
International T14 Clutch (Rear Axle Weight Ratings of 52,000 lb and Less)	36	Unlimited	Unlimited	Unlimited	Unlimited
Towing (Vehicles with International T14 Clutch Failures Only) (Rear Axle Weight Ratings of 52,000 lb and Less)	36	Unlimited	Unlimited	Unlimited	Unlimited
International T14 Clutch (Rear Axle Weight Ratings Greater than 52,000 lb)	24	Unlimited	Unlimited	Unlimited	Unlimited
Towing (Vehicles with International T14 Clutch Failures Only) (Rear Axle Weight Ratings Greater than 52,000 lb)	24	Unlimited	Unlimited	Unlimited	Unlimited
Transmission (Rear Axle Weight Ratings of 52,000 lb and Less)	36	300,000	480,000	Unlimited	Unlimited
Transmission (Rear Axle Weight Ratings Greater than 52,000 lb)	12	Unlimited	Unlimited	Unlimited	Unlimited
Front Axle Assembly (Rear Axle Weight Ratings of 52,000 lb and Less)		300,000	480,000	Unlimited	Unlimited
Front Axle Assembly (Rear Axle Weight Ratings Greater than 52,000 lb)		Unlimited	Unlimited	Unlimited	Unlimited
Rear Axle and Differential (Rear Axle Weight Ratings of 52,000 lb and Less)	36	300,000	480,000	Unlimited	Unlimited
Rear Axle and Differential (Rear Axle Weight Ratings Greater than 52,000 lb)		Unlimited	Unlimited	Unlimited	Unlimited
Federal Emissions Coverage (Medium/Heavy, Heavy Duty Diesel Engine)		100,000	160,000	Unlimited	Unlimited
Federal Emissions Coverage (Medium/Heavy, Heavy Duty Diesel Engine Non-Navistar)		100,000	160,000	Unlimited	Unlimited
Greenhouse Gas Emissions Coverage	60	100,000	160,000	Unlimited	Unlimited

#### International Diesel Engine Coverage Includes:

Engine block, cylinder heads, internally lubricated components, fuel pump, high-pressure pump, turbocharger, water pump, air compressor, injectors/nozzles; electronic engine modules, engine relays, engine sensors and regulators required for electronic engine operation, and certain aftertreatment components. Excluding: attaching accessories (e.g., fan clutch, alternator, starter, etc.), and externally mounted electrical and filtration systems.

#### **♠** INTERNATIONAL

### LIMITED WARRANTY FOR HX \*Effective with vehicles built January 01, 2021 or later

#### What is Not Included Under Basic Coverage

#### Components/Items

- Components warranted by their respective manufacturers (such as non-International brand engines, Cummins engines, Allison transmissions, Agility fuel systems, lubricants, etc.)
- Tires warranted by the tire manufacturer having defects in materials and workmanship that do not cause non-compliance with GHG regulations. International warrants tires installed as original equipment on this vehicle only against defects in materials and workmanship that cause the vehicle to fail to comply with GHG regulations. This vehicle tire emissions warranty is valid for two (2) years or 24,000 miles (38,000 km), whichever occurs first.
- Bodies, equipment, and accessories installed by other than authorized International employees at International manufacturing plants
- · Front and rear axle alignment
- Front and rear axle coverage excludes brakes, wheel ends, axle shafts, controls and attachments

#### Repairs & Maintenance

- Maintenance-related items/repairs, or those needed as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- · Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension

#### Other

- · Vehicles sold and/or operated outside the United States and Canada
- This exception does not apply to vehicles that meet current US EPA emission standards, which were sold by an International dealer located in Mexico, if the vehicle is authorized by the US DOT to operate in long-haul, cross-border transportation and the vehicle is only operated in the United States, Canada, and Mexico
- · Vehicles/components that have had unauthorized alterations or modifications
- · Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by International.

#### **Obtaining Service**

Return this vehicle to any International dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International dealer for name and address change information.

Note: The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International® dealer for details.

#### **Disclaimer**

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER.

No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

#### **Telematics Data Disclosure**

Your International vehicle may include an activated telematics subscription service. By accepting this Limited Warranty, you consent to our collection and use of data from your vehicle as set forth at www.oncommandconnection.com on behalf of yourself and any vehicle operators and passengers. International or its affiliates will collect and send diagnostic and system data from your vehicle and use it for various purposes as further set forth in our Privacy Policy, posted at www.oncommandconnection.com, such as improving the uptime for your vehicle, improving our vehicles in the future, and reducing warranty events. If you choose not to allow International to access your data, you may suspend your subscription at www.InternationalTrucks.com/Opt-Out.

#### **♠** INTERNATIONAL

# LIMITED WARRANTY FOR HX \*Effective with vehicles built January 01, 2021 or later

#### **Record of Ownership**

Date Delivered to User (DTU)

Upon receipt of new vehicle by original owner, complete	the following:				
I have read this Warranty Brochure and fully understand t Warranty and I accept the terms described herein.	the warranty coverage. I acknowledge that I h	have received a copy of the Owner's Limited			
Customer Signature	Date				
Owner's Address	City	State/Prov Postal Code			
Truck Model	Vehicle Identification Numl	Vehicle Identification Number			
Engine Model Number	Engine Serial Number	Engine Serial Number			

IMPORTANT: The information contained in this Warranty Policy explains the coverage provided on your new International vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.

Odometer Reading at Delivery

Page: 3 of 3 Revised 13/06/2025